

Hiwall indoor unit for MULTI Split systems

WHY CHOOSE SCHIARA 2?

- ✓ Smart management as standard: via smartphone with the NetHome Plus App and voice control setup with Amazon Alexa and Google Assistant.
- ✓ Purification filter: active against odours, dust, VOC, pollen, spores, bacteria and virus
- ✓ Extremely wide air distribution thank to the 180° motorized louver rotation
- ✓ SINGLESplit/MULTISplit compatible

180° LOUVER

Horizontal louver can rotate with a 180° angle, bigger than a standard unit.



PURIFICATION FILTER

Clean the air from smells, dangerous gas (VOC), microbes (bacteria, virus, spores) and other particles.



CASCADE

Quick cooling function that let the horizontal louver rotate automatically



COMFORT



Stepless Indoor Fan Speed



Anti-cold air



Multidirectional Airflow



180° louver



Cascade

RELIABILITY



Self-diagnosis Function



Auto Defrosting

CONVENIENCE



Wi-Fi Control



Single/Multi Compatible



Auto-restart



0,5°C Temperature Regulation



Voice control compatible

ENERGY SAVING



Sleep

HEALTH



High Density filter




Purification filter



Wi-Fi NWMX (standard)



REMOTE CONTROL RG10X1-G2HS-BGEF (standard)



IE2-Y

technical data

Indoor unit				IE2-Y	27M	35M
Code					87012283	89092266
Cooling capacity	Nominal			Btu/h	9.000	12.000
				kW	2,6	3,5
Heating capacity	Nominal			Btu/h	10.000	13.000
				kW	2,9	3,8
Dimensions	Unit	L x D x H	mm	920x211x321	920x211x321	920x211x321
	Packaging	L x D x H	mm	1005x385x295	1005x385x295	1005x385x295
System weight	Unit/Packaging		kg	11,30/14,16	11,30/14,16	11,30/14,16
Air filter	Type		-		PUF	
Airflow			m ³ /h	700/515/425		700/515/425
Sound power			dB(A)	53		53
Sound pressure level			dB(A)	40/32,5/21,5		40/32,5/21,5
Operating Voltage Range	Cooling	Indoor T	°C		16~32	
	Heating	Indoor T	°C		0~30	
Refrigerant piping	External diameters	Liquid-Gas	mm	Φ6,35 - Φ9,52		Φ6,35 - Φ9,52
			inch.	1/4" - 3/8"		1/4" - 3/8"
Control system	Infrared remote control		-		RG10X1-G2HS-BGEF	
	Settable temperature		°C		16~30	
Power supply	Voltage/Frequency/Phases		V/Hz/n°		230 / 50 / 1	

Fan speed: Hi=High; Mid=Medium; Lo=Low; Si=Silent
PUF= Purificator

Test conditions:

according to EN14511 / EN12102

Cooling: indoor air temperature 27°C DB/19°C WB; outdoor air temperature 35°C DB/24°C WB;

Heating: indoor air temperature 20°C DB/15°C WB; outdoor air temperature 7°C DB/6°C WB.

Data declared according to UE 626/2011 delegated regulation

accessories

Standard	
RG10X1-G2HS-BGEF	Wireless remote controller for SCHIARA 2 indoor units
NWMX	Wi-fi kit for indoor units